



Kobelco 7150

6370 Long Dr.
 Houston, Texas 77087
 Phone: 713-641-3330
 Fax: 713-645-3765
 cranes@consolidatedcrane.com
 www.consolidatedcrane.com

BOOM LIFTING CAPACITIES (with carbody counterweights and an additional counterweight)

Rated Loads in Thousand of pounds of 360 degrees Working Area
 (with carbody counterweights and an additional counterweight)

THIS CAPACITY CHART IS FOR REFERENCE USE ONLY

Boom Length ft (m) Operating radius ft (m)		170	180	190	200	210	220	230	240	250	260	270	Boom Length ft (m) Operating radius ft (m)	
39-4 (12)		103.3	95.9	88.1									39-4 (12)	
45-11 (14)		92.1	88.8	83.9	81.5	79.8	73.8	66.8					45-11 (14)	
52-6 (16)		81.3	78.4	74.5	78.4	77.6	72.0	65.2	59.7	55.1	50.2	44.7	52-6 (16)	
59-0 (18)		72.7	70.1	66.5	72.5	74.2	69.0	63.4	58.2	53.7	48.7	43.4	59-0 (18)	
65-7 (20)		65.6	63.2	59.9	65.0	70.1	67.2	60.8	56.6	52.4	47.6	42.3	65-7 (20)	
72-2 (22)		59.7	57.3	54.4	58.6	61.5	61.5	59.0	54.2	50.0	46.2	41.0	72-2 (22)	
78-9 (24)		54.4	52.4	49.6	53.3	54.4	54.4	54.4	52.6	47.1	43.2	39.6	78-9 (24)	
85-4 (26)		49.1	48.0	45.6	48.5	48.7	48.7	48.7	48.0	44.3	40.1	37.2	85-4 (26)	
91-10 (28)		44.5	43.8	41.8	44.3	43.8	43.8	43.6	43.2	41.4	37.4	34.6	91-10 (28)	
98-5 (30)		40.5	39.9	38.5	40.3	39.6	39.6	39.6	39.0	38.8	34.8	32.1	98-5 (30)	
105-0 (32)		37.0	36.3	35.4	36.5	36.1	36.1	35.9	35.4	35.0	32.6	29.7	105-0 (32)	
111-7 (34)		33.9	33.2	32.8	33.5	33.0	33.0	32.8	32.1	31.9	30.4	27.5	111-7 (34)	
118-1 (36)		31.3	30.6	30.4	30.8	30.2	30.2	30.2	29.5	29.3	27.9	25.3	118-1 (36)	
124-8 (38)		29.1	28.4	27.9	28.4	27.7	27.7	27.7	27.1	26.8	25.5	22.9	124-8 (38)	
131-3 (40)		26.4	26.2	25.7	26.2	25.5	25.5	25.5	24.9	24.6	23.3	21.3	131-3 (40)	
137-10 (42)		23.8	23.8	23.5	24.4	23.8	23.8	23.5	22.9	22.7	21.8	19.8	137-10 (42)	
144-4 (44)		21.3	21.6	21.3	22.7	22.0	22.0	21.8	21.1	20.9	20.5	18.7	144-4 (44)	
150-11 (46)		18.9	19.4	19.4	21.1	20.5	20.5	20.2	19.6	19.4	18.9	17.1	150-11 (46)	
157-6 (48)			17.1	17.4	19.6	18.9	18.9	18.7	18.0	17.8	17.4	16.3	157-6 (48)	
164-1 (50)				15.4	18.2	17.6	17.6	17.4	16.7	16.5	16.0	14.9	164-1 (50)	
170-7 (52)					17.1	16.5	16.5	16.3	15.6	15.4	14.9	13.8	170-7 (52)	
177-0 (54)					16.0	15.4	15.4	15.2	14.5	14.1	13.6	12.7	177-0 (54)	
183-9 (56)						14.3	14.3	14.1	13.4	13.0	12.3	11.9	183-9 (56)	
190-3 (58)							13.4	13.2	12.3	11.9	11.2	10.8	190-3 (58)	
196.1 (60)								12.1	11.4	11	10.3	9.9	196-1 (60)	
203-5 (62)									11.2	10.3	9.9	9.4	203-5 (62)	
210-0 (64)										9.4	9.0	8.5	210-0 (64)	